



RIME PENDANT LAMP - EU VERSION

TAF STUDIO ON THE DESIGN "Designing simple things is often one of the hardest things to do. We wanted to create a simple lamp with a glass shape, giving it a soft expression while making its top and pendant tube as subtle as possible. We were inspired by the shape of acorns for the gentle lines of the pendant while hinting towards the shaded expression of ice and rime for the glass of the design, allowing for the light to shine slightly through with a refined touch. The Rime Pendant Lamp brings a timeless yet modern perspective to the archetypal light through its translucent shade and graphic form."

Ø 12 cm / 4.7"





Ø 45 cm / 17.7''





DESIGNED BY / YEAR OF DESIGN TAF Studio / 2020

ABOUT THE DESIGNER

TAF Studio is a Stockholm-based design and architecture studio, founded by Gabriella Gustafson and Mattias Ståhlbom. The duo works within product and interior design.

CATEGORY Pendant lamp

ENVIRONMENT

Indoor

COUNTRY OF PRODUCTION Poland

DESCRIPTION

Bringing a new perspective to the glass pendant lamp through its mouthblown, translucent glass that has been sandblasted for a refined surface expression. Designed with a characteristic form, complemented by a powder-coated top-part, pendant tube and cord in a matching color for a subtle touch.

MATERIAL

Mouthblown glass shade. Aluminum, powder coated top-piece and pendant tube. PVC cord.

CORD LENGTH 400 cm / 13'1"

BULB INCLUDED Ø12: Yes Ø25, Ø37, Ø45: No

CEILING CAP INCLUDED

Yes - white Øl2 & Ø25: Ø 9 cm / 3.5" H 5,6 cm / 2.2" Ø37 & Ø45: Ø II cm / 4.3" **H** 3,5 cm / I.4"

DIMMABLE FUNCTION

Yes, if dimmable bulb is used.

CLEANING AND CARE

Clean with a moist cloth. If necessary use a little dish soap on the cloth.



RIME PENDANT LAMP - EU VERSION

220 - 240V

50/60Hz

Max. 25W

220 - 240V

50/60Hz

Max. 40W

220 - 240V

50/60Hz

IP2O

Class I

l x E27

Max. 60W

IP2O

Class II


I x FI4

IP2O

Class II

I x G9





RIME PENDANT LAMP This luminaire is compatible with bulbs of the energy classes: The luminaire is sold 0

LAMP RATING Ø12

Voltage Frequency IP Rating Classification Socket

LAMP RATING Ø25

Voltage Frequency **IP** Rating Classification Socket

LAMP RATING Ø37

Voltage Frequency **IP** Rating Classification Socket

LAMP RATING Ø45

Voltage	220 - 240V
Frequency	50/60Hz
IP Rating	IP2O
Classification	Class I
Socket	l x E27
	Max. 60W

BULB SPECIFICATION Ø12

G9 LED ltem Watt 3 W Lumen 190 lm/W 2700K Kelvin Lumen Maintenance 20.000h CRI 90 Dimmable Yes **Risk Group** Except

BULB RECOMMENDATION Ø25

Lamp base F14 Ø45 X 80 mm Dimensions Light source shape P45 Recommended light output Light source type

400-800 lm (6-10 W LED) LED with opal or frosted diffuser

BULB RECOMMENDATION Ø37

Lamp base E27 Dimensions Ø60 X IIO mm Light source shape A6O Recommended 750-1500 lm (8-12 W LED) liaht output Light source type LED with opal or frosted diffuser

BULB RECOMMENDATION Ø45

Lamp base E27 Dimensions Light source shape A67 Recommended light output Light source type

Ø77 X 145 mm 750-1500 lm (8-12 W LED) LED with opal or frosted diffuser

GENERAL STANDARDS & CERTIFICATES

EU/UK

Low Voltage Directive - 2014/35/EU IEC 60598-I (EU deviations) IEC 60598-2-I (EU deviations)

Electromagnetic Compatibility (EMC) Directive - 2014/30/EU

ECO Design Directive - 245/2009/EC

ROHS Directive - 2011/65/EU

WEEE Directive - 2012/19/EU

REACH Directive - EC/1907/2006

Μυυτο